


JOB NAME:	
CONTRACTOR:	DATE:



STINGER® NAILPAC

Description: 1" STINGER NailPac, 1" x .083, Ring Shank, Electro-Galv
Size: Ø0.083 x 1 inch Steel Nail with Ø1 inch Plastic Cap
Head Type: Full-Round, Flat



APPLICATION For indoor or outdoor applications
 Designed for installation of synthetic underlayment, roofing felt, and housewrap

FEATURES Cap/Nail passes Florida Building Code, Building 1507.1.1.1 and Residential R905.1.1.1
 Nail has ringed shank for improved holding power
 Collation has 200 caps per reel & 200 nails per coil

MATERIALS Nail made from low-carbon steel
 Cap made from HDPE plastic

COATINGS Nail has 11 micron electro-galvanized coating
 Cap requires no coatings

INSTALLATION Uses Stinger CN100 or CN100B Tool

PERFORMANCE VALUES Nail Tensile Strength 135-149 kpsi
 Nail Shear Strength 220-250 psi

FASTENER DIMENSIONS	Cap Dimensions		Cap Edge Lip	Nail Length	Nail Shank Dia.
	Cap Dia.	Cap Flat-to-Flat	Cap Edge Lip		
	D	A	H	L	W
	1 in	0.923 in	0.035 in	1 in	Ø 0.083 in

PRODUCT AVAILABLE

